



Aircraft Warning Light Fixture

ALJ-LIOL-2X (LOW Intensity)

TECHNICAL DATA

Type	ALJ-LIOL-2X (Low Intensity)
Degree of Protection	IP 66
Enclosure Material	Aluminum Alloy
Enclosure Color	Body: RAL1028 - Lid: RAL 2004
Protective Cover/Bowl	Polycarbonate
Permissible Ambient Temperature	-30°C to +55°C
Entries	Direct Entries, ¼ NPT or M25 / ½ NPT or M20 (Other threads available on request)
Weight	Approx. 2.2 kg
Mounting Type	2 Fixing Holes for M6/M8 Screws (Other mounting brackets are available on request)
Rated Voltage	180 ~260 VAC (24 VDC/AC on Request)
Power Consumption(± 10 %)	Average Power Consumption<10W (40W Impulse on 35ms)
Frequency	50/60 Hz
Rated Current	45mA
EMC Protection	Yes
Over-Voltage Protection:	2.5 KV
Starting Time (at 230 V,50 Hz)	0.8 S
Luminous intensity	Flashing/Steady32 cd
Connecting Terminal	Direct Connection to Terminal L, N, PE – 4 mm2
Light Source	Modular LED Board
Color	Red LED / Red bulb
Light Angel	360
Operating Condition	Indoor/Out door
Flashing Characteristics	40-60FPM
Lifetime	100.000 Hours

All information may be revised or changed by SHOMAL at anytime without prior notice or explanation.

