



Aircraft Warning Light Fixture

FLBA-MIOL-2X (Medium Intensity)

TECHNICAL DATA

Type	FLBA-MIOL-2X (Medium Intensity)
Degree of Protection	IP 66
Enclosure Material	Aluminum Alloy
Enclosure Color	Grey RAL 7032 (Body), RAL 7043 (Cover)
Protective Cover/Bowl	Borosilicate Glass
Permissible Ambient Temperature	-30°C to +55°C
Entries	Direct Entries, 1*M20 (Other threads are available on request by adaptor)
Weight	Approx. 11 kg
Mounting Type	2*Slotted Fixing Brackets with necessary M8/M10 bolts and nuts (Other mounting brackets are available on request)
Rated Voltage	180 ~260 VAC (24 VDC/AC on Request)
Power Consumption(± 10 %)	Average Power Consumption<20W (100W Impulse on 35ms)
Frequency	50/60 Hz
Rated Current	100mA
EMC Protection	Yes
Over-Voltage Protection:	2.5 KV
Starting Time (at 230 V,50 Hz)	0.8 S
Luminous intensity	Flashing 2000 cd
Connecting Terminal	Direct Connection to Terminal L, N, PE – 4 mm ²
Light Source	Modular LED Board
Color	Red LED / Red bulb
Light Angel	360
Operating Condition	Indoor/Out door
Flashing Characteristics	20-60 FPM
Lifetime	100.000 Hours
Construction	2000 cd Main / 2000 cd Reserve

All information may be revised or changed by SHOMAL at anytime without prior notice or explanation.



www.shomal.com